

Equipped with additional tools, a Brokk becomes even more profitable for your business. Grapples, scabblers, buckets, drills and other devices greatly expand the machine's efficiency and versatility. Here's our wide and ever-expanding range of original Brokk attachments:



SB302



■ BREAKERS

	Hitting power*	Blows/min	Weight	Made for
SB 52	101 J/Nm	960 – 1 700	55 kg/121 lbs	Brokk 60
SB 152	254 J/Nm	840 – 1 900	140 kg/309 lbs	Brokk 100, 120D, 160
SB 202	406 J/Nm	850 – 1 800	200 kg/441 lbs	Brokk 160
SB 302	610 J/Nm	600 – 1 400	310 kg/683 lbs	Brokk 280
SB 452	855 J/Nm	550 – 1 250	441 kg/972 lbs	Brokk 400, 800
SB 552	1 048 J/Nm	650 – 1 150	520 kg/1 146 lbs	Brokk 400
MB 1200	2 709 J/Nm	340 – 680	1 200 kg/2 646 lbs	Brokk 800

*Actual output, impact energy class (Joule/Nm)

A variety of chisels and tools can be fitted to the breakers. Other breaker brands can also be used on Brokk machines. Contact your local Brokk dealer or Brokk AB for information.

PTA-09



■ SIDE ANGLING DEVICE**

	Angle	Weight*	Made for
PTA-04,5	±60°	140 kg/309 lbs	SB 102/Brokk 100, 120D
PTA-06	±70°	215 kg/474 lbs	SB 152/Brokk 160
PTA-07	±70°	330 kg/728 lbs	SB 202/Brokk 280
PTA-09	±55°	555 kg/1 224 lbs	SB 302/Brokk 400

*With breaker

** Requires one extra hydraulic function



CONCRETE CRUSHERS**



CC520

	Jaw opening	Rebars	Crushing force	Weight	Made for
CC260	250 mm/9.8 in	Ø16 mm/0.6 in	220 kN/22 t/ 49 Klbf	82 kg/ 181 lbs	Brokk 60
CC340	343 mm/14 in	Ø30 mm/1.2 in	360 kN /37 t/ 81 Klbf	160 kg/ 353 lbs	Brokk 100, 120D
CC430*	431 mm/17 in	Ø30 mm/1.2 in	382 kN/39 t/ 86 Klbf	265 kg/ 584 lbs	Brokk 160
CC520*	540 mm/21 in	Ø30 mm/1.2 in	466 kN/48 t/ 105 Klbf	407 kg/ 897 lbs	Brokk 280
CC700*	650 mm/26 in	Ø30 mm/1.2 in	680 kN/69 t/ 153 Klbf	610 kg/ 1 345 lbs	Brokk 400, 800

*Option pulverizing pads

**Free rotation



METAL SHEARS*



BMS 250-H

	Cutting force	Jaw opening	Weight	Made for
HCS6	214 kN/22 t/48 Klbf	267 mm/10.5 in	56 kg/123 lbs	Brokk 60, 100, 120D
HCS7	312 kN/32 t/70 Klbf	357 mm/14.1 in	158 kg/348 lbs	Brokk 100, 120D, 160
CC420S	740 kN/75 t/166 Klbf	145 mm/6 in	300 kg/661 lbs	Brokk 160, 280
CC700S	1 840 kN/188 t/414 Klbf	268 mm/11 in	695 kg/1 532 lbs	Brokk 400, 800
BMS 100	647 kN/66 t/145 Klbf	195 mm/7.7 in	380 kg/838 lbs	Brokk 160, 280
BMS 140	863 kN/88 t/194 Klbf	290 mm/11.4 in	645 kg/1 422 lbs	Brokk 400
BMS 250-H	1 353 kN/138 t/304 Klbf	375 mm/14.8 in	1 360 kg/2 998 lbs	Brokk 800
MC 200	490 kN/50 t/110 Klbf	200 mm/7.9 in	120 kg/265 lbs	Brokk 100, 160, 120D
TC 120	662 kN/68 t/149 Klbf	120 mm/5 in	305 kg/672 lbs	Brokk 160, 280

*Requires one extra hydraulic function
Rotator with continuous rotation



BUCKETS*

2501



Volume	Width	Weight	Made for
20 l/0.7 cu ft	330 mm/13 in	20 kg/44 lbs	Brokk 60
60 l/2.1 cu ft	520 mm/20.5 in	61 kg/134 lbs	Brokk 100, 120D
80 l/2.8 cu ft	690 mm/27.2 in	76 kg/168 lbs	Brokk 160
250 l/8.8 cu ft	930 mm/36.6 in	195 kg/430 lbs	Brokk 280, 400, 800
700 l/24.7 cu ft	1 050 mm/41.3 in	650 kg/1 433 lbs	Brokk 800

*See load diagram for each Brokk machine




C05HPX



CLAMSHELL BUCKETS*

	Volume	Opening range	Width	Weight	Made for
C02H-25	25 l/0.9 cu ft	725 mm/28.5 in	250 mm/9.8 in	110 kg/243 lbs	Brokk 100, 120D
C03H-35	65 l/2.3 cu ft	880 mm/34.6 in	350 mm/13.8 in	175 kg/386 lbs	Brokk 160
C05H-40	115 l/4.1 cu ft	1 090 mm/42.9 in	400 mm/15.7 in	210 kg/463 lbs	Brokk 280
C05HPX-60	170 l/6.0 cu ft	1 110 mm/43.7 in	600 mm/23.6 in	375 kg/827 lbs	Brokk 400
C08HPX-80	300 l/10.6 cu ft	1 250 mm/49.2 in	800 mm/31.5 in	580 kg/1 279 lbs	Brokk 800

*See load diagram for each Brokk machine
Rotator with continuous rotation
Requires one extra hydraulic function



MULTI PURPOSE GRAPPLES*

	Volume	Opening range	Width	Weight	Made for
A02H-30	35 l/1.2 cu ft	835 mm/32.9 in	300 mm/11.8 in	152 kg/335 lbs	Brokk 100, 120D, 160
A03H-40	70 l/2.5 cu ft	1 475 mm/58.1 in	390 mm/15.4 in	285 kg/628 lbs	Brokk 280
A05HPX-40	100 l/3.5 cu ft	1 400 mm/55.1 in	400 mm/15.7 in	410 kg/904 lbs	Brokk 400
A09HPX-50	200 l/7.1 cu ft	1 650 mm/65 in	500 mm/19.7 in	675 kg/1 488 lbs	Brokk 800



A05HPX-40

Orange Peel Grapple

KM651-4 180	180 l/6.4 cu ft	1 450 mm/57.1 in	1 070 mm/42.1 in	520 kg/1 146 lbs	Brokk 400
KM651-4 250	250 l/8.8 cu ft	1 550 mm/61 in	1 285 mm/50.6 in	870 kg/1 918 lbs	Brokk 800



KM651-4

*See load diagram for each Brokk machine
Requires one extra hydraulic function
Rotator with continuous rotation

G30



SORTING & DEMOLITION GRAPPLES*

	Jaw opening	Weight	Made for
G30	300 mm/11.8 in	42 kg/93 lbs	Brokk 60
G50	400 mm/15.7 in	140 kg/309 lbs	Brokk 100, 120D, 160
D02H-30	790 mm/31.1 in	133 kg/293 lbs	Brokk 100, 120D, 160
D03HPX-40	975 mm/38.4 in	310 kg/683 lbs	Brokk 280
D05HPX-50	1 135 mm/44.7 in	400 kg/882 lbs	Brokk 400
D09HPX-60	1 400 mm/55.1 in	595 kg/1 312 lbs	Brokk 800



D02H

*See load diagram for each Brokk machine
Requires one extra hydraulic function
Rotator with continuous rotation

ER 100



SCABLERS

	Cutting depth**	Width	Weight	Made for
RT 15-40	0-5 mm/0-0.2 in	120 mm/4.7 in	66 kg/146 lbs	Brokk 60
RT 15-90*	0-5 mm/0-0.2 in	203 mm/8 in	102 kg/225 lbs	Brokk 100, 120D, 160
ER 50****	0-30 mm/0-1.2 in	480 mm/18.9 in	160 kg/353 lbs	Brokk 100, 120D, 160
ER 100****	0-65 mm/0-2.6 in	610 mm/24 in	345 kg/761 lbs	Brokk 160, 280, 400, 800
ER 250****	0-80 mm/0-3.1 in	680 mm/26.8 in	545 kg/1 202 lbs	Brokk 400***

*Cover and suction on request

**Data depending on concrete quality

***B800 on request depending on requirement

****Requires drainage hose

BCP250



PLANERS

	Cutting depth	Width	Weight	Made for
BCP 215* **	0-5 mm/0-0.2 in	215 mm/8.5 in	230 kg/507 lbs	Brokk 100, 120D
BCP 250* **	0-5 mm/0-0.2 in	265 mm/10.4 in	345 kg/761 lbs	Brokk 160
BCP 350* **	0-5 mm/0-0.2 in	335 mm/13.2 in	600 kg/1 323 lbs	Brokk 280, 400
PLB 300*	0-50 mm/0-2 in	300 mm/11.8 in	452 kg/996 lbs	Brokk 280, 400

*Available with cover and suction

**Requires extra hydraulic function, drainage hose, cable kit, counter weight in some occasions

Requires load holding. On request

PLB 300



TE 160-100



DRILLING EQUIPMENT***

	Length	Drill diameters	Drill steel size	Max. stroke length**	Weight	Made for
TE 160-100	1 910 mm/ 75.2 in	33 – 42mm 1.3 – 1.7 in	R25	1 000 mm/ 3.3 ft	225 kg/ 496 lbs	Brokk 100, 120D, 160
TE 260-180*	2 900 mm/ 114.2 in	33 – 52 mm 1.3 – 2 in	R32	1 830 mm/ 6 ft	415 kg/ 915 lbs	Brokk 160, 280, 400
TE 260-240*	3 500 mm/ 137.8 in	33 – 52 mm 1.3 – 2 in	R32	2 435 mm/ 8 ft	432 kg/ 952 lbs	Brokk 280, 400
TE 360-240*	3 590 mm/ 141.3 in	42 – 76 mm 1.7 – 3 in	R32	2 435 mm/ 8 ft	644 kg/ 1 420 lbs	Brokk 400, 800

*Extension rod drilling

**Per stroke with open centerizer

***Requires drainage hose, cable kit, counter weight in some occasions, water or airflushing

Brokk Beam Grapple



■ BEAM GRAPPLE*

	Jaw opening	Beam weight	Weight	Made for
Brokk Beam Grapple	250 mm/9.8 in	B280: 90 kg/198 lbs B400: 500kg/1 102 lbs B800: 500 kg/1 102 lbs	320 kg/705 lbs	Brokk 280, 400, 800

*Requires load holding valves with hose burst function
Requires two extra hydraulic functions

Brokk Shot Crete



■ SHOT CRETE*

	Concrete hose (di)	Gunning pressure	Air pressure	Weight	Made for**
Brokk Shot Crete	45 mm/1.8 in	Depend on concrete pump	Depend on concrete pump	180 kg/397 lbs	Brokk 280, 400, 800

*Requires two extra hydraulic functions
**Other models on request

BCS10



■ CUT OFF SAW*

	Saw disk diameter**	Cutting depth***	Weight	Made for
BCS 8	400 mm/16 in	170 mm/7 in	62 kg/137 lbs	Brokk 60
BCS 10	400 mm/16 in	170 mm/7 in	65 kg/143 lbs	Brokk 100, 120D, 160
BCS 25****	800 mm/31 in	260 mm/10 in	192 kg/423 lbs	Brokk 160
BCS 35****	800 mm/31 in	260 mm/10 in	195 kg/430 lbs	Brokk 280, 400, 800

*Requires one extra hydraulic function
**Different saw disks available depending on material
***With new saw disk
****Requires drainage hose



C20



■ SPLITTERS

	Length****	Drill hole diameter	Splitting force theoretical	Total weight*****	Made for
C20 V**	1 833 mm/72 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	455 kg/ 1 003 lbs	Brokk 280*- 400
C20 H***	1 790 mm/70 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	460 kg/ 1 014 lbs	Brokk 280*- 400
C20 J**	2 110 mm/83 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	440 kg/ 970 lbs	Brokk 280*- 400

*Require counter weight
**Requires one extra hydraulic function
***Requires two extra hydraulic functions
****Value without wedge set. Value without mounting kit
*****With mounting kit and wedge set